

## 2100K High CRI LED Strip 240LEDs per meter - 19.2W/m – powered by SMD3528

- CIE Colour Space: 3 SDCM
- Very Warm White 2100K - Length: 5m per roll
- High density LED strip series – 240 LEDs/m
- Ideal for use in living areas – high brightness applications
- Excellent colour rendering: CRI Ra typ. 90
- Fair efficiency: 78 lm/w
- long operating life L70 > 36,000 h at Tc < 80 °C
- Cutting points at every 25mm (6 LEDs)
- With high-quality 3M double adhesive tape



Please observe the installation and safety instructions at [https://www.hiline-lighting.co.uk/gb/index.php?controller=attachment&id\\_attachment=114](https://www.hiline-lighting.co.uk/gb/index.php?controller=attachment&id_attachment=114) !

### PHOTOMETRIC DATA

	HL-LS3528HA-240VWW-IP00-24V
Typ. colour temperature	2100 K
Light colour	Very Warm White
Typ. luminous flux per meter	1500 lm/m
Efficiency	78 lm/w
Energy efficiency class	A++
Typ. colour rendering index	90
LED beam angle	120 °
Lifetime L70	>36000 h

### ELECTRICAL DATA

	HL-LS3528HA-240VWW-IP00-24V
Operating voltage	24V - DC
Typ. power per meter	19.2 W/m

### MECHANICAL DATA

	HL-LS3528HA-240VWW-IP00-24V
Length stripe	5000 mm
Width stripe	10 mm
Height stripe	1.4 mm
Number of LEDs per cut	6
Number of cuts	200 per 5m roll
Length per cut	25 mm
Type of protection	IP 00

	HL-LS3528HA-240VWW-IP00-24V
Cut	One section - 25mm

## FURTHER DATA

	HL-LS3528HA-240VWW-IP00-24V
<b>Max. operable length<sup>1</sup></b>	5000 mm
<b>Storage temperature</b>	-30° C ~ +80° C
<b>Max. temperature Tc<sup>2</sup></b>	80° C

<sup>1</sup>The value given applies to the application of rated voltage at the first module section. When using a supply line, the maximum operable length changes depending on the supply line length and its cross section. At "www.hiline-lighting.co.uk" you will find an overview for orientation and calculation for volt drop.

<sup>2</sup>Tc=Case temperature at Tc point, this should be measured in a thermally stable state

## Certificates and Standards CE & RoHS

LVD Directive 2014/35/EU  
EMC Directive 2004/108/EC  
RoHS Directive 2011/65/EU  
RTTE Directive 99/5/EC

The following harmonized standards were applied:  
EN60598-1:2008+A11:2009, EN60598-2-20:2010+AC:2010  
EN55015:2013, EN61547:2009, EN61000-4-2:2009, EN61000-4-3:2006+A2:2010  
EN1122:2001, EPA3050B, EPA3052, EPA3540C, EPA3060A  
IEC62321: 2013

© 2018 Hi-Line Lighting Ltd. All rights reserved.

This document contains information relating to the Hi-Line Lighting portfolio and is intended for companies who may be interested in developing their product offering. Note that the information provided is subject to change. Hi-Line Lighting does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract.