

Bendable IP00 LED Strip – 14.4W/m – powered by SMD2835 – 5m roll

- Roll length 500 cm (tails both ends)
- Bendable LED strip indoor series
- Ideal for use in living areas, coves and signage applications
- Good color rendering: CRI Ra typ. 80
- Good efficiency: up to 100 lm/W at 6000 K
- Long operating life L70 > 36,000 h at Tc < 80 °C
- Constant brightness and consistency over the entire length
- With high-quality 3M double adhesive tape



Please observe the installation and safety instructions at https://www.hiline-lighting.co.uk/gb/index.php?controller=attachment&id_attachment=114 !

PHOTOMETRIC DATA

	HL-BLS2835HB-60WW-IP00-24V	HL-BLS2835HB-60NW-IP00-24V	HL-BLS2835HB-60CW-IP00-24V
Typ. colour temperature	2700 K	4000 K	6000 K
Light colour	Warm White	Natural White	Cool White
Typ. luminous flux per meter	1320 lm/m	1380 lm/m	1440 lm/m
Efficiency	92 lm/w	96 lm/w	100 lm/w
Energy efficiency class	A++		
Typ. colour rendering index	80		
LED beam angle	120 °		
Lifetime L70	>36000 h		

ELECTRICAL DATA

	HL-BLS2835HB-60WW-IP00-24V	HL-BLS2835HB-60NW-IP00-24V	HL-BLS2835HB-60CW-IP00-24V
Operating voltage	24 V DC		
Typ. power per meter	14.4 W/m		

MECHANICAL DATA

	HL-BLS2845HB-60WW-IP00-24V	HL-BLS2835HB-60NW-IP00-24V	HL-BLS2835HB-60CW-IP00-24V
LED Strip Length (One Roll)	5000 mm (5 meters)		
FCB Width	8 mm		
LED Strip Height	1,4 mm		
Number of LEDs per cut	6		
Number of cuts	50		
Length per cut	100 mm		
Type of protection	IP 00		

	HL-BLS2835HB-60WW-IP00-24V	HL-BLS2835HB-60NW-IP00-24V	HL-BLS2835HB-60CW-IP00-24V
Cut	Cut Length 100 mm, 2700K	Cut Length 100 mm, 4000K	Cut Length 100 mm, 6000K


FURTHER DATA

	HL-LS3528B-60WW-IP00-24V	HL-LS3528B-3K60WW-IP00-24V	HL-LS3528B-60NW-IP00-24V
Max. operable length¹	10000 mm		
Storage temperature	-30° C ~ +80° C		
Max. temperature Tc²	80° C		

¹The value given applies to the application of the rated voltage at the first module section. When using a supply line, the maximum operable length changes depending on the supply line length and its cross section. At www.hiline-lighting.co.uk you will find an orientation and calculations for voltage drop.

² Tc= Case Temperature at Tc point. This should be measured in the thermally stable state.

TECHNICAL DRAWING



Certificates and Standards CE & RoHS

LVD Directive 2014/35/EU
EMC Directive 2004/108/EC
RoHS Directive 2011/65/EU
RTTE Directive 99/5/EC

The following harmonized standards were applied:

EN60598-1:2008+A11:2009, EN60598-2-20:2010+AC:2010
EN55015:2013, EN61547:2009, EN61000-4-2:2009, EN61000-4-3:2006+A2:2010
EN1122:2001, EPA3050B, EPA3052, EPA3540C, EPA3060A
IEC62321: 2013

© 2018 Hi-Line Lighting Ltd. All rights reserved.

This document contains information relating to the Hi-Line Lighting portfolio and is intended for companies who may be interested in developing their product offering. Note that the information provided is subject to change. Hi-Line Lighting does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract.